cincoze™

CV-210

10.1” Rugged Industrial Display Module

Key Benefits

- **10.1” WXGA Display** with 1280 × 800 resolution, 500 cd/m² brightness and 178° viewing angles
- **Projected Capacitive Touchscreen** with anti-glare coating and wet touch tracking
- **IP66 Front Panel Protection** with rugged die-cast construction for industrial environments
- **Long-Life LED Backlight** rated for up to 50,000 operating hours
- **Modular CDS Architecture** supporting configurable industrial panel PC and touch monitor systems



Overview

The CV-210 is a 10.1-inch slim-bezel industrial display module designed for compact HMI applications. Its WXGA touchscreen combines projected capacitive technology, anti-glare coating and wet touch tracking for reliable operation in demanding indoor environments. Rugged die-cast construction, an IP66-compliant front panel, wide viewing angles and a 50,000-hour LED backlight support long-term operation. Cincoze Convertible Display System (CDS) technology enables integration with compatible computing or monitor modules, providing flexible configuration and simplified maintenance.

Certifications

IP66 FC CE CDS Convertible Display System





Specifications

Model Name	CV-210C
Display	
LCD Size	▪ 10.1" (16:10)
Max. Resolution	▪ 1280x800
Brightness (cd/m2)	▪ 500
Contrast Ratio	▪ 800 : 1
LCD Color	▪ 16.7M
Pixel Pitch (mm)	▪ 0.1695 (H) x 0.1695 (V)
Viewing Angle (H-V)	▪ 178 / 178
Backlight LED Life Time	▪ 50,000 hrs (LED Backlight)
Touch Screen	
Touch Type	▪ Projected Capacitive
Anti-Glare	▪ V
Wet Touch Tracking	▪ V
Physical	
Dimension (W x D x H)	▪ 259.3 x 179.9 x 63.4 mm
Weight Information	▪ 1.45 kg
Mechanical Construction	▪ Die-Casting Flat Surface
Power	
Power Consumption	▪ 6.45 W (Typ.)
Environment	
Front Panel Protection	▪ IP 66 Compliant
Operating Temperature	▪ -20°C - 70°C (-4°F to 158°F) - With Industrial Grade peripherals; Ambient with air flow
Storage Temperature	▪ -40°C - 85°C (-40°F to 185°F)
Relative Humidity	▪ 90% RH @ 40°C (non-condensing)
EMC	▪ CE, UKCA, FCC, ICES-003 Class A
EMI	▪ CISPR 32 Conducted & Radiated: Class A ▪ EN/BS EN 55032 Conducted & Radiated: Class A ▪ EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A ▪ EN/BS EN61000-3-3 Voltage fluctuations & flicker ▪ FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A
EMS	▪ EN/IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV ▪ EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 3 V/m ▪ EN/IEC 61000-4-4 EFT: AC Power: 1 kV; DC Power: 0.5 kV; Signal: 0.5 kV ▪ EN/IEC 61000-4-5 Surges: AC Power: 2 kV; Signal: 1 kV ▪ EN/IEC 61000-4-6 CS: 3V ▪ EN/IEC 61000-4-8 PFMF: 50 Hz, 1A/m ▪ EN/IEC 61000-4-11 Voltage Dips & Voltage Interruptions: 0.5 cycles at 50 Hz
Industrial Environment	▪ EMC: - EN/BS/IEC 61000-6-4: 2019 Class A - EN/BS/IEC 61000-6-2: 2019

Railway	▪ EMC: EN 50155: 2021 Clause 4.4.6, 13.4.9 (w/ M1101 only) - EN 50121-1 : 2017 - EN 50121-3-2: 2016 + A1: 2019

External Layout

Front



Rear



Dimensions



Unit: mm

Ordering Information

Available Models

Model No.	Description
CV-210C-R10	10.1" TFT WXGA 16:10 Slim Bezel Display Module with Projected Capacitive Touch & AG Coating

Package Checklist

- CV-210C Display Module x 1
- Panel Mounting Kit x 6

Delivering end-to-end, like no one else.
Bring us your challenge & experience the difference.

Corporate & EMEA Headquarters
Fareham, Hampshire, UK
+44 (0) 1489 866 066
sales-emea@captec-group.com

Subsystems Engineering UK
Farnborough, Hampshire, UK
+44 (0) 1252 512 919
sales-cse@captec-group.com

Canada Headquarters
Cambridge, ON, Canada
+1 (519) 650 4000
sales-canada@captec-group.com

USA Headquarters
Buffalo, NY, USA
+1 (519) 650 4000
sales-usa@captec-group.com

captec-group.com

260828_01 © Captec Group Plc. 2026 All rights reserved. All products and company names listed are trademarks or trade names of their respective companies.